

## DATASHEET

---

The extra large Ambu BlueSensor R features a conductive wet gel, offset connector and a Ag/AgCl sensor that ensures stable signal quality.

The electrode is suitable for short-term application and is gentle to the skin.

### Key benefits


- Offset connector mitigates the impact on signal quality from external forces like pulling of lead wires and pressure on electrodes
- Offset connector allows the user to connect and disconnect the lead wire without applying pressure to the patient or the sensor area, which reduces the risk of gel spreading and adhesive detachment from skin
- Conductive wet gel lowers skin impedance effectively and immediately
- Wet gel optimises contact between skin and electrode
- Adhesive is gentle to the skin and suitable for short-term application
- Ag/AgCl sensor ensures stable signal quality
- Visible release liner can help prevent medical accidents for both users and patients

# Ambu® BlueSensor R

ECG Electrode  
Single use



Wet gel



Foam  
backing



Silver  
sensor

**BlueSensor**

**Ambu**

## SPECIFICATIONS

### Dimensions

Electrode size (length x width in mm)	57 x 48
Skin contact size (diameter in mm)	48
Adhesive area (in mm <sup>2</sup> )	1555

### Sensor

Sensor material	Silver/silver chloride (Ag/AgCl)
Gel system	Wet gel
Gel area/measuring area (in mm <sup>2</sup> )	254

### Electrical data (ANSI/AAMI)

AC impedance - typical	360 Ω
DC offset voltage - typical	0.38 mV
Defibrillation overload recovery - typical	10.47 mV
Rate of change of polarisation potential - typical	-0.17 mV/s
Combined offset instability and internal noise	1.9 µV
Bias current tolerance (over 8 hours)	4.1 mV

## MATERIALS

### Electrode

Bio-compatible	Yes
Sponge	Polyurethane foam (PUR)
Backing material	Polyvinyl chloride foam (PVC)
Skin adhesive	Acrylate
Upper part	Polyvinyl chloride film (PVC)
A connector fitting	Polypropylene (PP)
S connector (stud)	Stainless steel
Release liner	Polyethylene film (PE)/Amorphous Polyethylene Terephthalate (APET)

## AVAILABLE CONFIGURATIONS\*

Reference number	Units/liner	Units/pouch	Units/inner box	Units/outer box
R-00-S/3	1	3	252	504
R-00-S/4	1	4	500	1000
R-00-S/5	1	5	500	1000
R-00-S/7	1	7	504	1008
R-00-S/10	1	10	500	1000
R-00-A/25	1	25	500	1000
R-00-S/25	1	25	500	1000

R-00-S ■ Product ■ Wire length ■ Connector

\*some configurations may not be available worldwide

## CONNECTORS



S = Stud



A = 4 mm fitting

## FEATURES



Printed release liner

### Environment

Electrode is not made with natural rubber latex

Packaging is PVC-free

### X-ray & MRI

Radiolucent	No
MR Conditional	No

### Shelf life

Opened pouches	1 month
Unopened pouches*	24 months

\*from date of production

### Packaging

Pouch (outer/middle/inner layers)	Polyester/ Aluminium/ Polyethylene
Boxes	Cardboard

### Options

Non-wired connectors S, A

### Precaution

Single use only

# Ambu

### Ambu Australia Pty Ltd

Unit 5, 2 Daydream Street,  
Warriewood  
NSW 2102

Tel: 1300 233 118

aussales@ambu.com

www.ambuaustralia.com.au

CE US: Rx only