Ambu® Neuroline 710



Key Benefits

- Special "duck foot" design ensures excellent adhesion
- Flexible soft material
- Repositionable
- · Ag/AgCl sensor for best trace quality
- Available in different leadwire configurations

Recommended applications

- Intraoperative Monitoring (IOM)
- Surface Electromyography (EMG)
- Nerve Conduction Studies (NCS)
- Electronystagmography (ENG)
- Electro-Oculography (EOG)
- Polysomnography (PSG)
- Evoked Potentials (EP)
- · Reference electrode

Ambu® Neuroline 710

Ambu Neuroline 710 is a multiple purpose disposable neurology electrode that can be used for all neurological examinations where the electrodes are placed outside the hair zone. The Ambu Neuroline solid gel electrode is selfadhesive, and it is easy to reposition.

The solid gel electrode is made of a very soft and flexible material, which ensures patient comfort and trace quality even during sleep studies. The 710 electrode is available with white or colour-coded lead wires in different lengths.



Specifications

Dimensions					
Electrode size (L x W in mm)	28 X 20				
Skin contact size (L x W in mm)	28 X 20				
Adhesive area (in mm²)	490				
Height excluding connector/wire (in mm)	1				
Sensor					
Sensor material	Silver/silver chloride				
Gel system	Solid gel				
Sensor area (in mm²)	490				
Gel area/measuring area (in mm²)	490				
Environment					
PVC-free electrode	No				
Latex-free electrode	Yes				
PVC-free lead wire	No				
Latex-free lead wire	Yes				
PVC-free packaging	Yes				

Materials

Electrode				
Bio-compatible	Yes			
Sensor	Silver/silver chloride (Ag/AgCI)			
Outer carrier	Carbon filled polyvinyl chloride			
Outer adhesive	Solid gel			
Upper part	Non-woven polypropylene			
Lead-wire core	Flexible copper			
Lead-wire insulation	Polyvinyl chloride (PVC)			
Lead-wire connector	Brass/polypropylene (PP)			
Liner	Siliconized polyester film			
Packaging				
Pouches, inner layer	Polyethylene (PE)			
Pouches, centre layer	Aluminium (AI)			
Pouches, outer layer	Paper			
Boxes	Cardboard			

Connectors



K = 1,5 mm connector



J = 2 mm connector



SC = 0.7 mm connector



Storage temperature

Available configurations

Item No.	Lead wire length		Colour	Shelf life in months		Packaging		
	cm	inch		(unopened/open pouches)		pouch	box	carton
710 01-SC/12	10	4"		18	1	12	240	1920
710 02-SC/12	20	8"		18	1	12	240	1920
710 05-K/12	50	20"		18	1	12	240	1920
710 05-K/C/12	50	20"		18	1	12	240	1920
710 10-J/12	100	40"		18	1	12	120	960
710 10-K/12	100	40"		18	1	12	120	960
710 15-K/12	150	60"		18	1	12	120	960
710 15-K/C/12	150	60"		18	1	12	120	960

Directions

Prepare the skin using an abrasive. Degrease using alchohol swab. Peel the electrode from its protective backing and apply. The electrode can be repositioned several times for better results.

Precautions

Single patient use only. For monitoring and recording biopotential on the skin.

Tel.: 1300 233 118 Fax. 1300 156 526 aussales@ambu.com www.ambuaustralia.com.au Ambu Asia (Sales office)

Customer Services

Tel.: +604 252 9100 Fax. +604 644 8932 csasia@ambu.com