Ambu[®] Neuroline Monopolar

Neurology Needle Electrode - Single Use



Key Benefits

- Tip superior in its sharpness for low penetration resistance
- Extra-smooth coating for low friction and improved patient comfort
- Ergonomic hub design for easy and secure grip
- Wide range of colour-coded sizes to meet your needs
- Available with or without pre-attached lead wire

Indication for use

• Electromyography (EMG)

Ambu® Neuroline Monopolar Needles

Ambu Neuroline Monopolar needles provide low penetration resistance thanks to the sharp design. Moreover, the needles have a smooth surface coating which reduces friction when inserting and working in the target area. This significantly improves patient comfort.

The needles feature a colour-coded ergonomic hub, which is both ribbed and concave to provide better control and tactile feedback. The needles are made of stainless steel and feature an optimal combination of strength and flexibility.

Strength ensures that you quickly and efficiently penetrate the skin; flexibility facilitates fine adjustments within the target area. Our needles are available both with and without a pre-attached lead wire.

Ambu also offers an Ambu Neuroline Monopolar cable with a 76 cm (30") lead wire.



Specifications

Environment	
PVC-free electrode	Yes
Latex-free electrode	Yes
PVC-free lead wire	No
Latex-free lead wire	Yes
PVC-free packaging	Yes

Connectors



K = 1.5 mm connector






Materials

Electrode without lead wire	Electrode with lead wire
Stainless steel	Stainless steel
Low friction polymer	Low friction polymer
Copolymer of Acrylonitile, Butadi- ene, and Styrene (ABS)	Copolymer of Acrylonitile, Butadiene, and Styrene (ABS)
	Flexible Copper wire with PVC insulation
Stainless steel	Brass
Polyethylene (PE)	Polyethylene (PE)
1.0 Pin - connector	1.5 mm touch-proof (DIN 42 802)
EO-sterilized	EO-sterilized
Polyethylene terephthalate (PET)	
Polypropylene (PP)	
Paper	
Cardboard	
	Stainless steel Low friction polymer Copolymer of Acrylonitile, Butadiene, and Styrene (ABS) Stainless steel Polyethylene (PE) 1.0 Pin - connector EO-sterilized Polyethylene terephthalate (PET) Polypropylene (PP) Paper

Available configurations

Item No.	Len	gth	Calibre		Shelf life in months	Packaging		ng
	mm	inch	mm	n° calibre	(unopened pouches)	pouch	box	carton
1 742 25-36/40	25	1"	0.36	28G	36	1	40	320
742 38-36/40	38	1.5"	0.36	28G	36	1	40	320
742 38-45/40	38	1.5"	0.45	26G	36	1	40	320
742 50-45/40	50	2"	0.45	26G	36	1	40	320
742 75-50/40	75	3"	0.50	25G	36	1	40	320
1 743 25-36/40*	25	1"	0.36	28G	36	1	40	320
743 38-36/40*	38	1.5"	0.36	28G	36	1	40	320
1 743 38-45/40*	38	1.5"	0.45	26G	36	1	40	320
743 50-45/40*	50	2"	0.45	26G	36	1	40	320
743 75-50/40*	75	3"	0.50	25G	36	1	40	320







Storage temperature

Available cables

Item No.	Lead wire length		Shelf life in months	Needle socket	Connector	Packaging	
	cm	inch	unopened pouches	mm	mm	pouch	
□ 1744	76	30"	_	1.0	1.5 (DIN 42 802)	1	

The reusable Ambu Neuroline Monopolar cable has an orientation-free connection to the needle, strong flexible wire and fits most EMG equipment.

5, 2 Daydream Street Warriewood, NSW 2102 Tel. 1300 233 118 Fax 1300 156 526 aussales@ambu.com www.ambuaustralia.com.au